



FAUSTINI

ELEVATORI IDRAULICI
HYDRAULIC ELEVATORS STAPLER ÉLÉVATEURS HYDRAULIQUES



DUPLEX



Modello con sollevamento a doppio effetto.

Lifting double acting.

Hubstapler / 2 Teleskop-Schienen mit DW-Zylinder und Sicherheitsventil.

Levage double effet.







Traslatore laterale montato su boccole autolubrificanti.

Side translation installed on self-lubricating bushings.

Hydraulischer Seitenvershub mit selbstschmierende Teflonbüchsen.

Translateur latéral monté sur douilles auto-lubrifiantes.



MOD.	Portata Capacity Hubgewicht Capacité (Kg)	Altezza di sollevamento Lifting height Hubhöhe Hauteur de levage (mm)	Altezza d'ingombro Overall height Gesamthöhe Gerät Hauteur d'encombrement (mm)	 Kg			Cilindri di sollevamento Lifting cylinder Hubzylinder DW Levage par vérin
FE DBCH 16 	1700	2200	1800	400		2	2
	1700	2800	2100	440		2	2
	1700	3200	2300	470		2	2
	1700	3600	2500	500		2	2
	1700	4000	2700	530		2	2
	1700	4500	2950	570		2	2