



FAUSTINI

ELEVATORI IDRAULICI
HYDRAULIC ELEVATORS STAPLER ÉLÉVATEURS HYDRAULIQUES

DUPLEX



- Modello con sollevamento a doppio effetto.
- Lifting double acting.
- Hubstapler / 2 Teleskop-Schienen mit DW-Zylinder und Sicherheitsventil.
- Levage double effet.






Traslatore laterale montato su boccole autolubrificanti.

Side translation installed on self-lubricating bushings.

Hydraulischer Seitenvershub mit selbstschmierende Teflonbüchsen.

Translateur latéral monté sur douilles auto-lubrifiantes.



MOD.	Portata Capacity Hubgewicht Capacité (Kg)	Altezza di sollevamento Lifting height Hubhöhe Hauteur de levage (mm)	Altezza d'ingombro Overall height Gesamthöhe Gerät Hauteur d'encombrement (mm)	 Kg		Cilindri di sollevamento Lifting cylinder Hubzylinder DW Levage par vérin
 FE DC 13	1300	1600	1550	340	2	1
	1300	2000	1750	355	2	1
	1300	2500	2000	380	2	1
	1300	3000	2250	400	2	1
	1300	3200	2350	415	2	1
	1300	3600	2550	435	2	1
	1300	4000	2750	450	2	1